



Dimensions	310mm x 310mm x 458mm (h)		12.2in x 12.2in x 18.03in (h)
Weight	19,7 kg		43,4 lb
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz
Current Consumption	2,1 A		3,6 A
Compressor Power	1/4 HP		
Power Consumption (Cooling)	315 W	1080 Btu/h	
Power Consumption (Heating)	400 W	1365 Btu/h	
Cooling Capacity *	630 W	2150 Btu/h	
Min and Max Water Flow	500 l/h - 800 l/h	132 Usgal/h - 211 Usgal/h	
Air Flow	160 m ³ /h	5650 CFH	
Maximum Exchanger's Pressure	0,6 bar	8,7 PSI	
Ambient Temperature Range	5°C - 38°C	41°F - 100°F	
Certification	CE		
Protection Grade	IPX4		

* the value reported refers to the following condition: room temperature 30°C (86°F), water temperature 25°C (77°F)

Material:	Drawing: TK 1000 - technical data		
Thickness:	File: TK_1000_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1: 5	Date: 09/04/2015
Approved:	Via A.Sansovino, 35 48124 RAVENNA - ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Matteo		