

## **4RS-1 Cut Sheet**



### **Features**

- Individual Power Relay (25A for each outlet)
- 3-second Intervals as Time Delay for Reducing Start-Up Surges

### **Overview**

The 4RS-1 is a universal 4-outlet power expansion module. It can be used with any of TrolMaster's "plug-in" style device modules to expand the number of devices that can be controlled by the Hydro-x. A single 120-240 volt "trigger" cable on the 4RS-1 connects to your device / control module. When the device module is activated by the Hydro-x, the 4RS-1 trigger cable will turn on each of the 4 receptacles on the 4RS-1 with a 3 second time delay between each outlet being activated. That minimizes high start-up (inrush current) and allows up to 4 devices to be safely controlled. The 4RS-1 must be installed with a 120/240 volt power circuit (up to 50-amps @ 240vac). Three wire terminals inside the unit accept up to #6 AWG wire making connections to the power source easy.

## M

# **Product Specifications**



#### **Package Content**

1 x Expender Station 4

#### Main Power Voltage

240 V

#### **Receptacle Quantity**

4

#### **Max Relay Amperage**

25A

#### **Operating Temperature**

41-140°F

#### **Operating Humidity**


0-99% Noncondensing


#### **Packaging Dimensions**

275mm(L) x 170mm(W) x 95mm(H)

#### G.W. per pack

1.50kgs





Tech Support

Phone: 877-420-9876

Email: support@trolmaster.com



CONFORMS TO UL STD.61010-1 CERTIFIED TO CSA STD. C22.2#61010-1