Technical Data Sheet

CODE 16155

CA 200 MD

In-line centrifugal fans in metal





Certifications [FII EAC



G-Mark



CB TEST CERTIFICATE

Technical and performance data

Frequency (Hz)	50
Insulation class	II°
IP	44
Max absorbed current at Max speed (A)	0,70
Max absorbed current at Min speed (A)	0,60
Max absorbed power at Max speed (W)	155
Max ambient temperature for	50
continuous operation (°C)	
Nominal diameter (mm)	200
Power absorbed at 1st speed (W)	115
Voltage (V)	220-240
Weight (Kg)	6

Airflow at 1st speed (l/s)	228
Airflow at 1st speed (m³/h)	820
Max airflow at Max speed (l/s)	292
Max airflow at Max speed (m³/h)	1050
Max pressure at Max speed (mmH20)	48
Max pressure at Max speed (Pa)	471
Max RPM	2100
Min RPM	1700
Pressure at 1st speed (mmH20)	37
Pressure at 1st speed (Pa)	363
Sound pressure at 3 m - min speed Lp [dB (A)] 3m - min speed	43,8
Sound pressure at 3m at Max speed Lp	49,6

Dimensions

Size A (mm)	347
Size B (mm)	275
Size C (mm)	424
Size D (mm)	197
Size E (mm)	20
Size F (mm)	17

PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 16155

CA 200 MD

In-line centrifugal fans in metal




Description

- \bullet Pickled and phosphated steel housing with polyester powder-coated finish, resistant to the aggressive action of atmospheric agents.

 Nominal diameter 200 mm.
- 2 speed AC motor with thermal overload cutout and shaft turning in ball bearings, coupled to backward curved centrifugal impeller.
- \bullet Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.

 • Zinc-coated steel brackets for wall mounting.
- Speed adjustable through Vortice speed control.

Curves



Accessories



C 1.5 (COMANDO EL. 1.5 A)

Code 12966



C 2.5 (COMANDO EL.

2.5 A) Code 12967



KIT SCB (TRASF.E.C.)

Code 22481



CA-MU (STAFFE DI SOSTEGNO)



TRIO-CA Code 12869

Code 22674

PER INFORMAZIONI / FOR INFORMATION

Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com